

MODEL		TOP KFS-27.2				TOP KFS-27.3			
Protok Vazduha		1850 m <sup>3</sup> /h				1600 m <sup>3</sup> /h			
Ventilator		220V/50Hz P=0,155kW I=0,75A n=1270o/min.							
MODEL		TOP KFW-27.2				TOP KFW-27.3			
Režim vode	T <sub>ul.</sub> [°C]	Q [ kW]	T <sub>iz.</sub> [°C]	T <sub>para</sub> [°C]	?Pv [ Pa ]	Q [ kW]	T <sub>iz.</sub> [°C]	T <sub>para</sub> [°C]	?Pv [ Pa ]
1,5 bar	-15	<b>33,18</b>	38,5	112	44	<b>40,01</b>	59,7	112	51
	-10	<b>31,87</b>	41,4	112	44	<b>38,42</b>	61,7	112	51
	0	<b>29,24</b>	47,2	112	44	<b>35,26</b>	65,8	112	51
	10	<b>26,62</b>	53,0	112	44	<b>32,09</b>	69,9	112	51
	15	<b>25,30</b>	55,8	112	44	<b>30,51</b>	71,9	112	51
3 bar	-15	<b>39,24</b>	48,3	133	44	<b>47,24</b>	73,2	133	51
	-10	<b>37,92</b>	51,2	133	44	<b>45,65</b>	75,2	133	51
	0	<b>35,27</b>	56,9	133	44	<b>42,47</b>	79,3	133	51
	10	<b>32,63</b>	62,7	133	44	<b>39,29</b>	83,3	133	51
	15	<b>31,31</b>	65,5	133	44	<b>37,70</b>	85,4	133	51
5 bar	-15	<b>44,25</b>	56,4	152	44	<b>53,24</b>	84,3	152	51
	-10	<b>42,93</b>	59,3	152	44	<b>51,64</b>	86,4	152	51
	0	<b>40,27</b>	65,0	152	44	<b>48,45</b>	90,4	152	51
	10	<b>37,62</b>	70,7	152	44	<b>45,26</b>	94,5	152	51
	15	<b>36,29</b>	73,6	152	44	<b>43,66</b>	96,5	152	51

Dimenzije : 550 x 500 x 300 mm

Q [ kW]	- Toplotna moć kalorifera
T <sub>ul.</sub> [°C]	- Ulazna temperatura vazduha
T <sub>iz.</sub> [°C]	- Izlazna temperatura vazduha
T <sub>para</sub> [°C]	- Temperature pare na ulazu
q <sub>w</sub> [m <sup>3</sup> /h]	- Protok vode kroz kalorifer
? p [ kPa ]	- Pad pritiska na strani vode
?Pv [ Pa ]	- Pad pritiska na strani vazduha