

MODEL	TOP KFS-52.2					TOP KFS-52.3			
Protok Vazduha	4100 m <sup>3</sup> /h					3800 m <sup>3</sup> /h			
Ventilator	220V/50Hz P=0,24kW I=1,1A n=1320o/min.								
MODEL	TOP KFS-52.2					TOP KFS-52.3			
Režim vode	T <sub>ul.</sub> [°C]	Q [ kW]	T <sub>iz.</sub> [°C]	T <sub>para</sub> [°C]	?Pv [ Pa ]	Q [ kW]	T <sub>iz.</sub> [°C]	T <sub>para</sub> [°C]	?Pv [ Pa ]
1,5 bar	-15	<b>73,00</b>	38,2	112	46	<b>92,31</b>	57,5	112	59
	-10	<b>70,11</b>	41,1	112	46	<b>88,66</b>	59,7	112	59
	0	<b>64,33</b>	46,8	112	46	<b>81,36</b>	63,9	112	59
	10	<b>58,56</b>	52,6	112	46	<b>74,05</b>	68,2	112	59
	15	<b>55,63</b>	55,5	112	46	<b>70,40</b>	70,3	112	59
3 bar	-15	<b>86,33</b>	47,9	133	46	<b>109,05</b>	70,7	133	59
	-10	<b>83,42</b>	50,7	133	46	<b>105,38</b>	72,8	133	59
	0	<b>77,61</b>	56,5	133	46	<b>98,04</b>	77,0	133	59
	10	<b>71,80</b>	62,3	133	46	<b>90,70</b>	81,3	133	59
	15	<b>68,89</b>	65,2	133	46	<b>87,02</b>	83,4	133	59
5 bar	-15	<b>97,41</b>	55,9	152	46	<b>122,91</b>	81,6	152	59
	-10	<b>94,49</b>	58,8	152	46	<b>119,22</b>	83,7	152	59
	0	<b>88,65</b>	64,6	152	46	<b>111,86</b>	87,9	152	59
	10	<b>82,81</b>	70,3	152	46	<b>104,49</b>	92,1	152	59
	15	<b>79,89</b>	73,2	152	46	<b>100,80</b>	94,2	152	59

Dimenzije : 750 x 700 x 375 mm

Q [ kW]	- Toplotna moć kalorifera
T <sub>ul.</sub> [°C]	- Ulazna temperatura vazduha
T <sub>iz.</sub> [°C]	- Izlazna temperatura vazduha
T <sub>para</sub> [°C]	- Temperature pare na ulazu
q <sub>w</sub> [m <sup>3</sup> /h]	- Protok vode kroz kalorifer
?p [ kPa ]	- Pad pritiska na strani vode
?Pv[ Pa ]	- Pad pritiska na strani vazduha